


CUSHOTRAC® Clamp[ON]™

The Universal
Quick-Fit Track
Pad for Excavators
and Cranes



UNIVERSAL FIT. EASIEST INSTALL.

- In stock, ready for immediate shipping
- Fastest & easiest installation – 2-4 hours for complete set
- Universal fit eliminates track modification & drilling holes
- ACS™ secures pad to grouser and prevents loosening
- Available in rubber and polyurethane



Active Clamping System™
Dual Clamping Mechanism

1.800.289.1456 | www.SuperiorTire.com

SUPERIOR
TIRE & RUBBER CORP.
HEAVY EQUIPMENT COMPONENTS



Management
Systems
Registered
to ISO 9001



GET A QUOTE IN 15 MINS OR LESS*

Simply scan the code with your phone, leave us your contact info and tell us the make and model of your machine!

*During standard business hours, excluding holidays, Monday - Friday, 8am - 5pm

THE FASTEST SOLUTION FOR SURFACE PROTECTION IN ANY APPLICATION



Eliminate Pad Loosening

ACS™ (Active Clamping System) automatically optimizes clamping force and continuously tightens.

Ensures 100% Work-Life with No Bond Failure

Proprietary Heat Activated Bonding Technology that provides the strongest bond between Poly/Rubber & steel plate, preventing costly premature product failure.

Application Specific

Proprietary extended wear-life polyurethane compound or premium high traction rubber compound.

INSTALLATION INSTRUCTIONS

Step 1


Completely remove both clamps from pad.

Lay pad on steel shoe so that coupling nuts sit down in valleys of shoe.



Step 2

Attach removed clamps back onto pad by hand tightening.



Step 3

Ensure pad is centered horizontally with an even gap on both sides between pad and clamp.

Steel-to-steel contact is required.



Step 4

Using a torque wrench, alternate tightening each bolt to 25-35 ft lbs to ensure pad stays centered on grouser shoe.



Popular Sizes

Most popular sizes listed.
Call 1.800.289.1456 for more information.

STANDARD (IN)	METRIC (MM)
12"	300mm
16"	400mm
18"	450mm
20"	500mm
24"	600mm
28"	700mm
29.5"	750mm
31.5"	800mm
33.5"	850mm
35.5"	900mm

APPLICATIONS

CUSHOTRAC® Clamp[ON]™ track pads are designed to provide quick and dependable surface protection whether it's required or recommended.

- Construction
- Crane Operations
- Waste Transfer
- Drilling Sites
- Trenchers

Rubber CUSHOTRAC® Clamp[ON]™ pads are not recommended for use in:

- Standing water or extremely muddy conditions
- Rough/jagged rock or broken concrete

For prolonged exposure to aggressive applications such as Demolition, we recommend using the Polyurethane Bolt-To-Link CUSHOTRAC® ReDDi™

100% Work-Life Guarantee*

All CUSHOTRAC® Track Pads are backed by an industry leading **100% Work-Life Guarantee**, to ensure you're getting the most cost saving advantages.



1.800.289.1456 | www.SuperiorTire.com



40 Scientific Road
Warren, PA 16365



**Refer to terms and conditions at www.superiortire.com.