CUSHOTHANE[®] The Universal Usage Wheel Specialist

High performance 95A compound

- Designed with a perfect balance to perform in 80% of applications
- Higher abrasion & chunk resistance resulting in a longer work-life

SUPER

CORP

Higher reliability and quality consistency

THE & RUBBER CORD






CUSHOTHANE®

Applications

Designed specifically to exceed the load and duty requirements of general fork truck load wheel usage while reducing cost.

The Universal Usage Wheel Specialist





High Performance 95A Compound - made from a high grade 95A polyurethane that is as premium as competitors' premium heavy load 95A compound

Longer Work-life - significantly higher abrasion and chunking resistance than the competitors standard compound, lower overall cost by reducing the number of wheels replaced and replacement labor paid during the life of the truck

Perfect Balance in Performance - designed to perform in a broad spectrum of usages with a perfect balance of dynamic properties, cut and tear resistance and abrasion resistance

Greater Reliability - that offers lower maintenance costs and minimal downtime



Universal Usage Examples -A perfect fit for Cushothane[®] load wheels

Reach Trucks & Order Pickers



Load Wheels

- · Clean, Dry Floors
- Guide Wheels
- Medium/Short Run
- Manufacturing Facility
- Big Box Stores
 (Not their DC)

Walkie & Rider Pallet Trucks



- Load Wheels
- Clean, Dry Floors
- Medium/Small Load
 Almost all Walkie Pallet Trucks
- · AIMOST AII WAIKIE FAIIEL MU

Stabilizing Caster Wheels

- Clean, Dry Floors
 Limited debris/dock plate
- Almost all Pallet Trucks
- Almost all Pallet Trucks
- Not for 4th wheel caster

[†]Refer to terms and conditions at www.SuperiorTire.com

Tires		
CL-I	CL-II	CL-III



Superior Select™

(Ships Same or Next Business Day[†])

OEM	OEM Part #	Dimensions
HYG®	524148750	3.25x4.5
Raymond®	632-069	3.25x5.937
Crown®	115033	5x4.125
Raymond®	1082408/06	4x2.5

Complete Load Wheel Kits

- · Complete drop in kit replacement
- · Save replacement time and cost
- Includes bearings pressed, with or without axle, spacers, washers and pins
- · Available in most popular load wheel sizes
- 3.25 x 3.25 3.25 x 4.5
- 3.25 x 5.91 3.25 x 5.984
- 3.25 x 6.5
- 4 x 2.5





40 Scientific Rd., Warren, PA 16365 1.800.289.1456 www.SuperiorTire.com